

# BT-THEATRE 200TW

B06030

## DESCRIPTION

Powerful 200W LED theater / TV Fresnel with tunable white ranging from 2800K to 6000K, combined with exceptional photometric / price ratio and good light output!

## FEATURES

- Powerful 200W LED theater Fresnel with **adjustable CCT**.
- Dual LED (100W 2800K + 100W 6000K) for tunable white with CCT ranging from 2800K to 6000K !
- The perfect all-round projector for TV-work, theatre, rental, exhibition booths!
- Exceptional photometric / price performance: CRI/Ra > 96, TLCI > 98, CQS > 96, Rf > 94, Rg > 100 (@3000K)
- Manual beam angle adjustment: 12° ~ 56° (field angle: 20° ~ 67°)
- Manual CCT presets while used in standalone: 2800K, 3000K, 3200K, 4000K, 4300K, 5600K, 6000K
- Color frame for use of color filters and eight-leaf barndoor included.
- No more heavy and expensive dimmer packs needed!
- Very silent operation: temperature controlled, low noise cooling fan.
- LCD-display to navigate easily through the setup menu!
- Manual or DMX-controlled: 5 different channel modes (8bit & 16bit dimming) for maximum flexibility.
- Can be used 1 channel DMX mode, with CCT-preset of your choice.
- Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE ! (Briteq® code: B04645)
- Flicker free TV-recordings thanks to adjustable LED refresh rate: 600 Hz to 4800 Hz!
- Manual dimming & zoom/focus control: easy projector alignment on the stage + use on exhibition booths.
- Selectable lamp behavior: halogen lamp (slow) or led (fast).
- Four dimmer curves: linear, square, inverse square, S-curve.
- In case of DMX failure, you can choose between manual, blackout and freeze mode.
- RDM-functionality for easy remote setup & monitoring: DMX addressing, channel mode, temperature, ...
- Lock function to avoid unwanted altering of the settings.
- Default factory settings + user settings can be saved/loaded.
- 3 & 5pin DMX in/outputs + PowerCON® compatible in/outputs for easy daisy chaining.



CCT 2800K SEAMLESS CCT-CONTROL CCT 6000K








[www.briteq-lighting.com](http://www.briteq-lighting.com) | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2020 by BEGLEC NV. All rights reserved.

## TECHNICAL SPECIFICATIONS

<b>General : Application</b>	Theatre
<b>General : Dimensions (cm)</b>	See drawing
<b>General : Weight (kg)</b>	7.2
<b>General : Powerinput</b>	AC 100 - 240V, 50/60Hz
<b>General : Energy Label</b>	No
<b>General : Power consumption W</b>	105
<b>General : Color</b>	black
<b>General : Display</b>	LCD
<b>General : Fixation</b>	M12
<b>General : IP rating</b>	indoor
<b>Control : Modes</b>	standalone, manual, DMX
<b>Control : manual</b>	Yes
<b>Control : Master/Slave</b>	No
<b>Control : SMART-DMX</b>	No
<b>Control : Standalone</b>	fixed
<b>Control : programmable</b>	No
<b>Control : upgradable software</b>	Yes
<b>Control : maximum DMX channels</b>	5
<b>Light : lamp socket</b>	none
<b>Light : Lux</b>	1850 (@ 5m beam 12°)
<b>Light : lamp</b>	COB
<b>Light : min. color temperature (K)</b>	2800
<b>Light : max. color temperature (K)</b>	6000
<b>Light : CRI</b>	95
<b>Light : colors</b>	White, Cold white, Warm white
<b>Light : mix colors</b>	Yes
<b>Light : functions</b>	manual focus, manual zoom
<b>Light : min. beam angle (°)</b>	12
<b>Light : max. beam angle (°)</b>	56
<b>Light : min. refresh rate (kHz)</b>	0.6
<b>Light : max. refresh rate (kHz)</b>	4.8
<b>Connections : input</b>	3 pin XLR, 5 pin XLR, PowerCon®, usb
<b>Connections : output</b>	3 pin XLR, 5 pin XLR, PowerCon®, usb
<b>Brand</b>	BRITEQ
<b>EANCode</b>	5420025660303



[www.briteq-lighting.com](http://www.briteq-lighting.com) | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2020 by BEGLEC NV. All rights reserved.