

## CC8 Stereo Set

## Cardioid True Condenser Microphone

Directional characteristic : Cardioid Frequency range: 20Hz - 20kHzSensitivity: 15 mV/PaEquivalent noise level: 16 dB SPLMax . SPL: 156 dB SPLHP filter:  $60 \text{ Hz} (2^{nd} \text{ order}), 120 \text{ Hz} (2^{nd} \text{ order})$ Switchable pad: -10 dB, -20 dBImpedance:  $275 \Omega$  (symmetrical) Load impedance:  $> 1 \text{ k}\Omega$ Supply voltage: 48 V (< 3 mA)Main Connector: XLR 3 pin Dimensions:  $140 \times 23 \times 23 \text{ mm}$ Weight: 160 g

## Setting new standards.

Designed, engineered and manufactured in Vienna, the CC8 is built around a small-diaphragm handmade true condenser capsule. With a max SPL of 156 dB and an equivalent noise level of 16 dB(A), the CC8 delivers a best-in-class dynamic range. Its rugged design and pristine results make it perfect for situations involving high sound pressure levels on stage, like cymbals & overheads, but also to pick up strings and other low dynamic acoustic instruments, classical ensembles and choirs in a wide variety of uses, including live performance, broadcasting, and studio recording. Inspired by a legend, and advanced for the modern recordist, the CC8 offers a linear frequency response and a natural and open sound with smooth and silky heights.

O ther features of the CC8 include:

- Out-of-the box match paired with any other CC8 due to factory calibration (+/-0,5dB @1kHz)
- Best-in-class off-axis response
- True condenser technology
- Transformerless design-classic sound using modern tech
- High precision cardioid pattern
- Metal housing, cap, and grille
- A switchable high-pass filter
- Pads (0, -10 dB, -20 dB) to enable to pick up sound up to 156dB

Content of Package 2x CC8 Microphone 2x OCH8 Mic clip 18mm 2x CCW8 Windscreen 1x SB1 Stereo Bar 1x Transport Case

E &OE. All information is correct at time of writing <u>www.austrianaudio.com</u>

