BEAMSPOT1-DMX NW

DESCRIPTION

Stylish DMX-controlled 15W White 4500K single beam projector, equipped with a very narrow 4° lens making it a very powerful tool for all kinds of applications.

FEATURES

- This compact, stylish 15W WHITE single beam projector is equipped with a very narrow 4° lens making it a very powerful tool for all kinds of applications: perfect for all kinds of effects on stage but also for simply illuminating mirror balls etc.
- Thanks to the included 10° & 45° filters this beauty can also be used for discotheques, exhibition booths, restaurants, shops, ... (perfect to light up small objects and small tables)
- Natural white 4500K color temperature with high CRI-factor (>90).
- Two different DMX-modes: 1 + 2 channels.
- RDM-functionality for easy remote setup: DMX addressing, channel mode
- The OLED-display assures easy navigation in the different setup menus.
- TV-Studio ready: no cooling fans and flicker free 1200Hz LED refresh rate
- Selectable lamp behavior: halogen lamp (slow) or led (fast)
- Four dimmer curves: linear, square, inverse square, S-curve
- In case of DMX failure you can choose between blackout and freeze mode
- Lock function to avoid unwanted altering of the settings.
- Default factory settings + user settings can be saved/loaded.
- 3pin DMX in/outputs and Neutrik[®] PowerCON[®] in/outputs for easy daisy chaining.





www.briteq-lighting.com | https://www.facebook.com/Briteq

SPECIFICATIONS

General: Application

Commercial lighting, DJ & Club,
Stage & Bental

General: Application Stage & Rental 17,2 x 19,6 x 12,5 cm

General: Weight (kg) 1.23

General : Powerinput AC 100 - 240V, 50/60Hz

General: Energy Label No **General: Power consumption W** 17 **General**: Color black **General: Display** No **General: Fixation** M10 **General: IP rating** indoor **Control: manual** Yes **Control: Master/Slave** Yes Control: DMX M/S No **Control: Standalone** fixed

Control: Type included remote
Control: optional remote
Control: programmable
Control: upgradable software
Control: maximum DMX channels
2

Light: lamp socket none

Light: Lux 1455 at 5m (angle 4°)

Light: lumen 200
Light: lamp LED
Light: min. color temperature (K) 4500
Light: max. color temperature (K) 4500
Light: CRI 90
Light: colors White
Light: mix colors No

Light : colors White
Light : mix colors No
Light : fixed gobos Light : rotating gobos Light : focus None
Light : zoom Manual
Light : iris No

Light : prism (# facets + rotating

y/n)

Light: min. beam angle (°)
4
Light: max. beam angle (°)
4

Connections : inputConnections : output
3 pin XLR, powercon, rdm
3 pin XLR, powercon

Connections: XLR 3 pin **Connections: XLR 5 pin** No **Connections: Power Conn.** Yes **Connections: midi** No **Connections: usb** No **Connections: wifi** No **Connections: bluetooth** No **Connections: artnet** No **Connections: rdm** Yes **Brand** BRITEQ

EANCode 5420025649568

Discontinued No

LUX (full on)		36	320	9080				40	35	2270			1455
BEAMSPOT1-DMX NW) '										
BEAM: 4°		L	6	H T	R E	SE	A R	C F		110			
DISTANCE (m) BEAM Ø (cm)		1 7			2 14		3 21			4 28			5 35





