## STAGE BEAMER FC -

## DESCRIPTION

Very powerful 14x5W OSRAM RGBW LED PROJECTOR for outdoor use.

## **FEATURES**

- Extra "16 bit TOUR"-mode with 16 bit colormixing (R, G, B en W controlled by 2 channels : coarse and fine).
- Very powerful RGBW LED projector based on 14 quadri-color 5W OSRAM LEDs:
  - Unwanted RGBW shadows are completely eliminated
  - Perfect and evenly spread color mixing, even at short range
  - Beam angle: 14°
  - IP65
- This LED projector is your first choice :To light up small, medium and large stages but also perfect for architectural lighting.
- Perfect alternative for traditional PAR64 projectors: only 65Watt power consumption at full output and no need for heavy dimmer packs!
- Different DMX operation modes: 4, 5, 6, 7, 9, 10 and 15ch
- Thanks to all kinds of special features this projector is the choice of professional light designers:
  - Color temperature presets 3200K ~ 10.000K
  - RGBW Calibration
  - Different dimmer curves
  - ID-addressing
  - Recall custom programs by DMX
  - Menu driven LED-display with password protection on the rear panel
  - Tempered glass lens protection
  - Special air-valve keeps humid outside: no condense inside the projector!
- The 1200Hz LED scan rate makes it also a perfect choice in TV studios (no interferences with TV-cameras)
- Completely silent: the projector is cooled by natural air convection so no noisy fans are needed!
- The lightweight aluminium housing uses a double hanging bracket so it can also be used as floor projector.







www.briteq-lighting.com | https://www.facebook.com/Briteq

## SPECIFICATIONS

**General: Application**Architectural, Stage & Rental,
Theatre

Theatre

**General : Dimensions (cm)** 24.5 x 20.5 x 24.5

**General: Weight (kg)** 4.96

**General: Powerinput** AC 100 - 240V, 50/60Hz

**General: Energy Label** No **General: Power consumption W** 65 **General: Color** black **General: Display** LED **General: Fixation** M10 **General: IP rating** outdoor **Control: manual** Yes Control: Master/Slave Yes **Control: SMART-DMX** No

**Control: Standalone** automatic, fixed

**Control: programmable** No **Control: upgradable software** No **Control: maximum DMX channels** 15 **Light: lamp socket** No Light: lamp LED **Light: colors RGBW Light: mix colors** Yes **Light: focus** No Light: zoom No Light: iris No **Light: min. refresh rate (kHz)** 1.2

Light : max. refresh rate (kHz)1.2Connections : inputip-powerlink connectorConnections : outputip-powerlink connector

Connections : outputip-powerlink conrBrandBRITEQEA NCode5420025655118

**Discontinued** No

LUX (full on) 18576	4644	2064	1161	743	516
STAGE BEAMER FC					
BEAM: 14°	LIGI	IT RESE	ARCH		
DISTANCE (m) 1	2	3	4	5	6
BEAM Ø (cm) 25	49	74	98	123	147





