# BEAMSPOT1-DMX WW

#### DESCRIPTION

Stylish DMX-controlled 15W Warm White 3200K single beam projector, equipped with a very narrow  $4^{\circ}$  lens making it a very powerful tool for all kinds of applications.

#### **FEATURES**

- This compact, stylish 15W WARM WHITE single beam projector is equipped with a very narrow 4° lens making it a very powerful tool for all kinds of applications: perfect for all kinds of effects on stage but also for simply illuminating mirror balls etc.
- Thanks to the included 10° & 45° filters this beauty can also be used for discotheques, exhibition booths, restaurants, shops, ... (perfect to light up small objects and small tables)
- Two different DMX-modes: 1 + 2 channels.
   RDM-functionality for easy remote setup: DMX addressing, channel mode.

• Natural white 3200K color temperature with high CRI-factor (>90).

- The OLED-display assures easy navigation in the different setup menus.
- TV-Studio ready: no cooling fans and flicker free 1200Hz LED refresh
- Selectable lamp behavior: halogen lamp (slow) or led (fast)
- Four dimmer curves: linear, square, inverse square, S-curve
- In case of DMX failure you can choose between blackout and freeze

  mode.
- Lock function to avoid unwanted altering of the settings.
- Default factory settings + user settings can be saved/loaded.
- 3pin DMX in/outputs and Neutrik® PowerCON® in/outputs for easy daisy chaining.





www.briteq-lighting.com | https://www.facebook.com/Briteq

### SPECIFICATIONS

General: Application Commercial, DJ & Club, Stage &

Rental

**General : Dimensions (cm)**  $17,2 \times 19,6 \times 12,5 \text{ cm}$ 

General: Weight (kg) 1.23

**General : Powerinput** AC 100 - 240V, 50/60Hz

**General: Energy Label** No **General: Power consumption W** 17 **General: Color** black **General: Display** No **General: Fixation** M10 **General: IP rating** indoor **Control: manual** Yes **Control: Master/Slave** Yes **Control: DMX MSL** No **Control: Standalone** fixed **Control: optional remote** RC-2 **Control: programmable** No **Control: upgradable software** Yes **Control: maximum DMX channels** 2

**Light : lamp socket Light : Lux**none

1455 at 5m (angle 4°)

Light: lamp
Light: min. color temperature (K)
Light: max. color temperature (K)
3200
Light: CRI
90
Light: colors

**Light: colors** Warm white **Light: mix colors** No **Light: focus** None Light: zoom None Light: iris No **Light**: min. beam angle (°) Light: max. beam angle (°) 45 Light: min. refresh rate (kHz) 3.6 **Light**: max. refresh rate (kHz)

**Connections : input**3 pin XLR, powercon, rdm **Connections : output**3 pin XLR, powercon

Brand BRITEQ

**EA NCode** 5420025649605

**Discontinued** No

## YOUR DEALER



www.briteq-lighting.com | https://www.facebook.com/Briteq