

**SHURE**<sup>®</sup>

LEGENDARY  
PERFORMANCE™

VP Camera-Mount  
Shotgun Microphones

**AUDIO, IN FOCUS.**



# VP83F

LensHopper™ **FLASH**

## Camera-Mount Shotgun Microphone with Integrated Flash Recording

Compact, rugged microphone for high-definition audio capture + integrated digital flash recording with DSLR cameras and HD camcorders.



VP83F LCD Screen and Controls



50Hz–20kHz 

- Detailed, high-definition audio with full low-end response
- Integrated digital flash recording (MicroSDHC, up to 32 GB) for WAV file capture at 24-bit/48 kHz sampling rate
- One-touch record button
- Dedicated headphone audio output for real-time headphone monitoring
- Intuitive menu and controls with five-position joystick and back-lit LCD screen
- Low cut filter & mic gain adjustments
- Integrated Rycote® Lyre® mount for robust shock isolation
- 10 hours battery life (record mode) from 2 AA alkaline batteries (included)
- Durable, all-metal construction with superior RF immunity
- Detachable 3.5 mm audio connector and foam windscreen included

# VP83

LensHopper™

## Camera-Mount Shotgun Microphone

Ultra-compact, rugged microphone for high-definition audio capture with DSLR cameras and HD camcorders.



VP83 Controls



50Hz–20kHz 

- Detailed, high-definition audio with full low-end response
- Easily accessible controls including three-position gain and low-cut filter switch
- Integrated Rycote® Lyre® mount for robust shock isolation
- 130 hours battery life from 1 AA alkaline battery (included)
- Durable, all-metal construction with superior RF immunity
- Attached 3.5 mm audio connector and foam windscreen included

### Accessories for VP83F and VP83

Foam Windscreen  
A83-W





Windjammer®  
A83-FUR





# Technical Specifications

## VP83F



<b>Type</b>	Electret Condenser
<b>Frequency Response</b>	50 - 20,000 Hz
<b>Polar Pattern</b>	Supercardioid/lobar
<b>Output Impedance</b>	Camera: 47 $\Omega$ Headphones: 5 $\Omega$
<b>Connector Type</b>	Camera: 3.5 mm (1/8") dual mono, unbalanced Headphones: 3.5 mm (1/8") dual mono
<b>Power Requirements</b>	2 AA batteries (Alkaline, NiMH, Lithium)
<b>Battery Life</b>	10 hours (record mode) from 2 AA alkaline batteries
<b>Construction</b>	Die-cast metal alloy body, satin-black finish
<b>Net Weight</b>	215 g (7.6 oz)

## VP83



<b>Type</b>	Electret Condenser
<b>Frequency Response</b>	50 - 20,000 Hz
<b>Polar Pattern</b>	Supercardioid/lobar
<b>Output Impedance</b>	171 $\Omega$
<b>Connector Type</b>	3.5 mm (1/8") dual mono, unbalanced
<b>Power Requirements</b>	1 AA battery (Alkaline, NiMH, Lithium)
<b>Battery Life</b>	130 hours from 1 AA alkaline battery
<b>Construction</b>	Die-cast metal alloy body, satin-black finish
<b>Net Weight</b>	133 g (4.7 oz.)

**United States, Canada,  
Latin America, Caribbean:**  
Shure Incorporated  
5800 West Touhy Avenue  
Niles, IL 60714-4608 USA

Phone: 847-600-2000  
Fax: 847-600-1212 (USA)  
Fax: 847-600-6446  
Email: info@shure.com

**Europe, Middle East, Africa:**  
Shure Europe GmbH  
Jakob-Dieffenbacher-Str. 12,  
75031 Eppingen, Germany

Phone: 49-7262-92490  
Fax: 49-7262-9249114  
Email: info@shure.de

**Asia, Pacific:**  
Shure Asia Limited  
22/F, 625 King's Road  
North Point, Island East  
Hong Kong

Phone: 852-2893-4290  
Fax: 852-2893-4055  
Email: info@shure.com.hk

**SHURE**<sup>®</sup>  
LEGENDARY  
PERFORMANCE™